




All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de c FCI. Droits de reproduction FCI.

PRODUCT NO.
10082141-XXXXXX



mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY		FCI		
ltr	ecn no	dr	date	linear	.X ± 0.30		projection	www.fciconnect.com			
A	T07-1178	WL	12/05/07		.XX ± 0.20			title	USB A TYPE PLUG,SMT		
B	T08-1010	WL	01/21/08		.XXX ± 0.10				(DIP HOLD-DOWN LENGTH 1.35mm)		
C	T08-1020	WL	02/05/08		angles	0° ± 2°					
D	T08-1036	WL	03/12/08	dr	WENDY CHEN	08/31/07	MM	product family		code	
				enr	ALLEN CHANG	08/31/07		size		TWN	
				chr	ALLEN CHANG	08/31/07		dwg no		sheet	
				appd	ALEX LIANG	08/31/07		A4		10082141	1 of 2
sheet index	revision sheet	D	D				scale				
		1	2								

ACAD

PDM: Rev:D

STATUS Released 2008 Printed Oct 09, 2008

cage code 2526

1 | 2

3

4

1 | 2

3

4

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriete de c FCI. Droits de reproduction FCI.



All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

NOTES:

1.MATERIAL:

SHELL: COLD ROLLED STEEL.
 HOUSING: THERMOPLASTIC, GLASS FIBER FILLED.
 UL 94V-0 RATED.

CONTACT: COPPER ALLOY

2.PLATING:

SHELL : NICKEL PLATED WITH 100u" MIN. OVER 120u" Cu.
 THEN COAT WITH A PROTECTIVE AGENT.
 CONTACT : 50u" MIN. NICKEL UNDER PLATED OVER ALL.
 100u" MIN. PURE MATTE TIN ON SOLDERING AREA.
 SELECTIVE GOLD PLATED ON CONTACT AREA.

3.PRODUCT SPEC NO: GS-12-545.

PACKAGE SPEC NO: GS-14-874.


4.PRODUCT NO. DESCRIPTION

10082141 - N 3 4 X LF

- LF: LEAD FREE VERSION
- 4: HOUSING COLOR
0: WHITE
1: BLACK
- X: HOUSING MATERIAL
4: LCP OR EQUIVALENT
- 3: CONTACT GOLD PLATED
3: 30u"
- N: SHELL PLATING
N: NICKEL

5.10082141-N34XLF: THE HOUSING WILL WITHSTAND EXPOSURE TO 260° PEAK TEMPERATURE FOR 10 SECONDS IN A CONVECTION, IR OR VAPOR PHASE REFLOW OVEN.

6.THIS PRODUCT (10082141-N34XLF) MEETS THE EUROPEAN UNION DIRECTIVE AS DESCRIBED IN GS-22-008.



RECOMMENDED P.C.B. LAYOUT
 TOLERANCE: ±0.05

5.10082141-N34XLF: THE HOUSING WILL WITHSTAND EXPOSURE TO 260° PEAK TEMPERATURE FOR 10 SECONDS IN A CONVECTION, IR OR VAPOR PHASE REFLOW OVEN.

6.THIS PRODUCT (10082141-N34XLF) MEETS THE EUROPEAN UNION DIRECTIVE AS DESCRIBED IN GS-22-008.

mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY		FCI		www.fciconnect.com	
ltr	ecn no	dr	date	linear	.X ± 0.30			projection	title			
D					.XX ± 0.20				USB A TYPE PLUG,SMT			
					.XXX ± 0.10				(DIP HOLD-DOWN LENGTH 1.35mm)			
				angles	0° ±2°			MM	product family		code	
				dr	WENDY CHEN	08/31/07	size		TWN			
				enr	ALLEN CHANG	08/31/07	dwg no		sheet			
				chr	ALLEN CHANG	08/31/07	A4		10082141		2 of	
				appd	ALEX LIANG	08/31/07	scale					
sheet	revision											
index	sheet											