


# MKP1V120 Series

Preferred Device

## Sidac High Voltage

### Bidirectional Triggers

Bidirectional devices designed for direct interface with the ac power line. Upon reaching the breakover voltage in each direction, the device switches from a blocking state to a low voltage on-state. Conduction will continue like a Triac until the main terminal current drops below the holding current. The plastic axial lead package provides high pulse current capability at low cost. Glass passivation insures reliable operation. Applications are:

- High Pressure Sodium Vapor Lighting
- Strobes and Flashers
- Ignitors
- High Voltage Regulators
- Pulse Generators
- Used to Trigger Gates of SCR's and Triacs
-  Indicates UL Registered — File #E116110
- Device Marking: Logo, Device Type, e.g., MKP1V120, Date Code

#### MAXIMUM RATINGS (T<sub>J</sub> = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Peak Repetitive Off-State Voltage (Sine Wave, 50 to 60 Hz, T <sub>J</sub> = -40 to 125°C) MKP1V120, MKP1V130, MKP1V160 MKP1V240	V <sub>DRM</sub> , V <sub>RPM</sub>	± 90 ± 180	V
On-State Current RMS (T <sub>L</sub> = 80°C, Lead Length = 3/8", All Conduction Angles)	I <sub>T(RMS)</sub>	± 0.9	A
Peak Non-repetitive Surge Current (60 Hz One Cycle Sine Wave, T <sub>J</sub> = 125°C)	I <sub>TSM</sub>	± 4.0	A
Operating Junction Temperature Range	T <sub>J</sub>	-40 to +125	°C
Storage Temperature Range	T <sub>stg</sub>	-40 to +150	°C


Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.



ON Semiconductor®

<http://onsemi.com>

**SIDACS (⚡)**  
**0.9 AMPS RMS**  
**120 – 240 V**



AA = Assembly Location  
xx = 12, 13, 16 or 24  
YY = Year  
WW = Work Week

#### ORDERING INFORMATION

Device	Package	Shipping†
MKP1V120RL	DO-41	5000 Tape & Reel
MKP1V130RL	DO-41	5000 Tape & Reel
MKP1V160	DO-41	1000 Units / Bulk
MKP1V160RL	DO-41	5000 Tape & Reel
MKP1V240	DO-41	1000 Units / Bulk
MKP1V240RL	DO-41	5000 Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Preferred devices are recommended choices for future use and best overall value.

## MKP1V120 Series

### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction-to-Lead Lead Length = 3/8"	$R_{\theta JL}$	40	°C/W
Lead Solder Temperature (Lead Length $\geq$ 1/16" from Case, 10 s Max)	$T_L$	260	°C

### ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ unless otherwise noted; Electricals apply in both directions)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

### OFF CHARACTERISTICS

Repetitive Peak Off-State Current (50 to 60 Hz Sine Wave) $V_{DRM} = 90\text{ V}$ , MKP1V120, MKP1V130 and MKP1V160 $V_{DRM} = 180\text{ V}$ , MKP1V240	$T_J = 25^\circ\text{C}$ $I_{DRM}$	–	–	5.0	$\mu\text{A}$
--	---------------------------------------	---	---	-----	---------------

### ON CHARACTERISTICS

Breakover Voltage $I_{BO} = 35\ \mu\text{A}$ MKP1V120 35 $\mu\text{A}$ MKP1V130 200 $\mu\text{A}$ MKP1V160 35 $\mu\text{A}$ MKP1V240	$V_{BO}$	110 120 150 220	– –	130 140 170 250	Volts
Peak On-State Voltage ( $I_{TM} = 1\text{ A Peak}$ , Pulse Width $\leq 300\ \mu\text{s}$ , Duty Cycle $\leq 2\%$ )	$V_{TM}$	–	1.3	1.5	Volts
Dynamic Holding Current (Sine Wave, 50 to 60 Hz, $R_L = 100\ \Omega$ )	$I_H$	–	–	100	mA
Switching Resistance (Sine Wave, 50 to 60 Hz)	$R_S$	0.1	–	–	k $\Omega$

### DYNAMIC CHARACTERISTICS

Critical Rate-of-Rise of On-State Current, Critical Damped Waveform Circuit ( $I_{PK} = 130\text{ Amps}$ , Pulse Width = 10 $\mu\text{sec}$ )	$di/dt$	–	120	–	A/ $\mu\text{s}$
---	---------	---	-----	---	------------------

# MKP1V120 Series

## Voltage Current Characteristic of SIDAC (Bidirectional Device)

Symbol	Parameter
$I_{DRM}$	Off State Leakage Current
$V_{DRM}$	Off State Repetitive Blocking Voltage
$V_{BO}$	Breakover Voltage
$I_{BO}$	Breakover Current
$I_H$	Holding Current
$V_{TM}$	On State Voltage
$I_{TM}$	Peak on State Current





Figure 1. Maximum Lead Temperature




Figure 2. Maximum Ambient Temperature




Figure 3. Typical On-State Voltage




Figure 4. Typical Power Dissipation

### THERMAL CHARACTERISTICS

# MKP1V120 Series




Figure 5. Thermal Response




Figure 6. Typical Breakover Voltage




Figure 7. Typical Holding Current





Figure 8. Pulse Rating Curve

# MKP1V120 Series

## PACKAGE DIMENSIONS

### AXIAL LEAD CASE 59-10 ISSUE U



NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. ALL RULES AND NOTES ASSOCIATED WITH JEDEC DO-41 OUTLINE SHALL APPLY
4. POLARITY DENOTED BY CATHODE BAND.
5. LEAD DIAMETER NOT CONTROLLED WITHIN F DIMENSION.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.161	0.205	4.10	5.20
B	0.079	0.106	2.00	2.70
D	0.028	0.034	0.71	0.86
F	----	0.050	----	1.27
K	1.000	----	25.40	----

STYLE 2:

NO POLARITY

# MKP1V120 Series

**ON Semiconductor** and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
**Phone:** 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Japan:** ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
**Phone:** 81-3-5773-3850

**ON Semiconductor Website:** <http://onsemi.com>

**Order Literature:** <http://www.onsemi.com/litorder>

For additional information, please contact your  
local Sales Representative.