

## General Description

The Sanrise SRT045N012HS is a low voltage power MOSFET, fabricated using advanced split gate trench technology. The resulting device has extremely low on resistance, low gate charge and fast switching time, making it especially suitable for applications which require superior power density and synchronous rectification.

The SRT045N012HS break down voltage is 45V and it has a high rugged avalanche characteristics. The SRT045N012HS is available in PDFN5\*6 and TO-220C and TO-263-2 packages.


## Features

- Ultra Low  
 $R_{DS(ON\_TYP)} = 1.07m\Omega$ , PDFN5\*6@ $V_{GS} = 10V$ .  
 $R_{DS(ON\_TYP)} = 1.8m\Omega$ , TO-220C @ $V_{GS} = 10V$ .  
 $R_{DS(ON\_TYP)} = 1.6m\Omega$ , TO-263-2@ $V_{GS} = 10V$ .
- Ultra Low Gate Charge,  $Q_g=73nC$  typ.
- Fast switching capability
- Robust design with better EAS performance
- EMI Improved
- Non-automotive Qualified

## Application

- Server/Telecom
- DC/DC Converter
- High Power Supply
- E-Tools
- BMS

## Symbol



TO-220C, TO-263-2

PDFN5\*6

Figure 1 Symbol of SRT045N012HS

## Package Type





Figure 2 Package Type of SRT045N012HS

**1.2mΩ, 45V, N-Channel Power MOSFET**
**SRT045N012HS**
**Ordering Information**


| Package  | Part Number         | Marking ID       | Packing Type |
|----------|---------------------|------------------|--------------|
| PDFN5*6  | SRT045N012HD56TR-GS | SRT045N012HD56GS | Tape & Reel  |
| TO-220C  | SRT045N012HTC-GS    | SRT045N012HTCGS  | Tube         |
| TO-263-2 | SRT045N012HS2TR-GS  | SRT045N012HS2GS  | Tape & Reel  |

**Absolute Maximum Ratings**

| Parameter   |                    | Symbol          | Rating     | Unit        |   |
|---|--------------------|-----------------|------------|-------------|---|
| Drain-Source Voltage                                |                    | $V_{DSS}$       | 45         | V           |   |
| Gate-Source Voltage                                 |                    | $V_{GSS}$       | ±20        | V           |   |
| Continuous Drain Current, Silicon                   | $T_C=25^{\circ}C$  | $I_D$           | PDFN56     | 228         | A |
|   |                    |                 | TO-220C    | 188         |   |
|   |                    |                 | TO-263-2   | 188         |   |
|   | $T_C=100^{\circ}C$ |                 | PDFN56     | 144         |   |
|   |                    |                 | TO-220C    | 119         |   |
|   |                    |                 | TO-263-2   | 119         |   |
| Pulsed Drain Current (Note 3)                       |                    | $I_{DM}$        | PDFN56     | 912         | A |
|   |                    |                 | TO-220C    | 752         |   |
|   |                    |                 | TO-263-2   | 752         |   |
| Power Dissipation ( $T_C = 25^{\circ}C$ )           |                    | $P_D$           | 131        | W           |   |
| Avalanche Destructive Energy, Single Pulse (Note 5) |                    | $E_{AS\_Limit}$ | 625        | mJ          |   |
| Avalanche Energy, Single Pulse (Note 4)             |                    | $E_{AS}$        | 121        | mJ          |   |
| Avalanche Energy, Repetitive (Note 3)               |                    | $E_{AR}$        | 0.3        | mJ          |   |
| Avalanche Current, Repetitive (Note 3)              |                    | $I_{AR}$        | 50.0       | A           |   |
| Continuous Diode Forward Current                    |                    | $I_S$           | 228        | A           |   |
| Diode Pulse Current                                 |                    | $I_{S,PULSE}$   | 912        | A           |   |
| Operating Junction Temperature                      |                    | $T_J$           | 150        | $^{\circ}C$ |   |
| Storage Temperature                                 |                    | $T_{STG}$       | -55 to 150 | $^{\circ}C$ |   |
| Lead Temperature (Soldering, 10 sec)                |                    | $T_{LEAD}$      | 260        | $^{\circ}C$ |   |

Note:

- Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
- Current Limited by Package.
- Repetitive Rating: Pulse width limited by maximum junction temperature
- $I_{AS}= 22A$ ,  $V_{DD}= 20V$ ,  $R_G= 25\Omega$ , Starting  $T_J= 25^{\circ}C$
- $I_{AS\_Limit}= 50.0A$ ,  $V_{DD}= 20V$ ,  $R_G= 25\Omega$ , Starting  $T_J= 25^{\circ}C$

**Thermal Resistance**

| Parameter                               |          | Symbol     | Min | Typ | Max  | Unit          |
|---|----------|------------|-----|-----|------|---------------|
| Thermal Resistance, Junction-to-Case    | PDFN5*6  | $R_{thJC}$ |     |     | 0.95 | $^{\circ}C/W$ |
|   | TO-220C  |            |     |     | 0.70 |               |
|   | TO-263-2 |            |     |     | 0.70 |               |
| Thermal Resistance, Junction-to-Ambient | PDFN5*6  | $R_{thJA}$ |     |     | 50   |               |
|   | TO-220C  |            |     |     | 62   |               |
|   | TO-263-2 |            |     |     | 62   |               |

**Electrical Characteristics**
 $T_J = 25^\circ\text{C}$ , unless otherwise specified.

| Parameter   | Symbol        | Test Conditions                                  | Min | Typ  | Max | Unit    |
|---|---------------|--|-----|------|-----|---------|
| <b>Statistic Characteristics</b>                              |               |  |     |      |     |         |
| Drain-Source Breakdown Voltage                                | $BV_{DSS}$    | $V_{GS}=0V, I_D=250\mu A$                        | 45  |      |     | V       |
| Zero Gate Voltage Drain Current                               | $I_{DSS}$     | $V_{DS}=45V, V_{GS}=0V$                          |     |      | 1   | $\mu A$ |
| Gate-Body Leakage Current                                     | Forward       | $I_{GSSF}, V_{GS}=20V, V_{DS}=0V$                |     |      | 2   | $\mu A$ |
|   | Reverse       | $I_{GSSR}, V_{GS}=-20V, V_{DS}=0V$               |     |      | -2  |         |
| Gate Threshold Voltage  | $V_{GS(TH)}$  | $V_{DS}=V_{GS}, I_D=0.25mA$                      | 2.0 | 3.0  | 4.0 | V       |
| Static Drain-Source On-Resistance                             | PDFN5*6       | $R_{DS(ON)}, V_{GS}=10V, I_D=60A$                |     | 1.07 | 1.2 | mΩ      |
|   | TO-220C       |  |     | 1.8  | 2.5 |         |
|   | TO-263-2      |  |     | 1.6  | 2.5 |         |
| Gate Resistance   | $R_G$         | $f=1MHz, \text{Open Drain}$                      |     | 1.1  |     | Ω       |
| <b>Dynamic Characteristics</b>                                |               |  |     |      |     |         |
| Input Capacitance   | $C_{ISS}$     | $V_{DS}=20V, V_{GS}=0V, f=1MHz$                  |     | 5.2  |     | nF      |
| Output Capacitance  | $C_{OSS}$     |  |     | 2.0  |     | nF      |
| Reverse Transfer Capacitance                                  | $C_{RSS}$     |  |     | 125  |     | pF      |
| Effective output capacitance, energy related <sup>NOTE5</sup> | $C_{O(er)}$   | $V_{GS}=0V, V_{DS}=0\dots 20V$                   |     | 3.1  |     | nF      |
| Effective output capacitance, time related <sup>NOTE6</sup>   | $C_{O(tr)}$   |  |     | 3.8  |     |         |
| Turn-on Delay Time  | $t_{d(on)}$   | $V_{DD}=20V, I_D=50A, R_G=1.6\Omega, V_{GS}=10V$ |     | 18   |     | ns      |
| Rise Time   | $t_r$         |  |     | 50   |     |         |
| Turn-off Delay Time   | $t_{d(off)}$  |  |     | 54   |     |         |
| Fall Time   | $t_f$         |  |     | 12   |     |         |
| <b>Gate Charge Characteristics</b>                            |               |  |     |      |     |         |
| Gate to Source Charge   | $Q_{gs}$      | $V_{DD}=20V, I_D=50A, V_{GS}=0 \text{ to } 10V$  |     | 24   |     | nC      |
| Gate to Drain Charge  | $Q_{gd}$      |  |     | 13   |     |         |
| Gate Charge Total   | $Q_g$         |  |     | 73   |     |         |
| Gate Plateau Voltage  | $V_{plateau}$ |  |     | 4.9  |     | V       |
| Gate Charge Total, sync FET                                   | $Q_g$         | $V_{DD}=0.1V, V_{GS}=0 \text{ to } 10V$          |     | 69   |     | nC      |
| <b>Reverse Diode Characteristics</b>                          |               |  |     |      |     |         |
| Drain-Source Diode Forward Voltage                            | $V_{SD}$      | $V_{GS}=0V, I_{SD}=50A$                          |     | 0.84 | 1.0 | V       |
| Reverse Recovery Time   | $t_{rr}$      | $V_R=20V, I_F=50A, dI_F/dt=100A/\mu s$           |     | 62   |     | ns      |
| Reverse Recovery Charge                                       | $Q_{rr}$      |  |     | 130  |     | nC      |
| Peak Reverse Recovery Current                                 | $I_{rrm}$     |  |     | 4.3  |     | A       |

Note:

- $C_{O(er)}$  is a fixed capacitance that gives the same stored energy as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 20V
- $C_{O(tr)}$  is a fixed capacitance that gives the same charging time as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 20V



TM

**Sanrise Tech**  
**尚阳通**

Sanrise Technology Limited Company

<http://www.sanrise-tech.com>**IMPORTANT NOTICE**

Shenzhen Sanrise Technology Co., LTD. reserves the right to make changes without further notice to any products or specifications herein. Shenzhen Sanrise Technology Co., LTD. does not assume any responsibility for use of any its products for any particular purpose, nor does Shenzhen Sanrise Technology Co., LTD. assume any liability arising out of the application or use of any its products or circuits. Shenzhen Sanrise Technology Co., LTD. does not convey any license under its patent rights or other rights nor the rights of others.

**Main Site:****- Headquarter**

Shenzhen Sanrise Technology Co., LTD.

A1206, Skyworth building, No. 008, gaoxinnan 1st Road,  
Gaoxin District, Yuehai street,, Nanshan District, ShenZhen,  
P.R.China

Tel: +86-755-22953335

Fax: +86-755-22916878

**- Shanghai Office**

Sanrise Technology Limited Company

Rm.401, Building B, No. 666, Zhangheng Road,  
Zhangjiang Hi-Tech Park, Shanghai, P.R.China

Tel: +86-21-68825918